ExconMobil

High-quality and safety for your dry cleaning business with DF-2000™ solvent

Energy lives here



In your dry cleaning business, you don't have to compromise on quality or safety with DF 2000 $^{\rm M}$ solvent.

Safe for use and for delivering excellent excellent dry cleaning performance, DF-2000 dry cleaning solvent is an effective alternative to other solvents such as perchloroethylene.

Key benefits of DF-2000 solvent

- Suitable on many sensitive fabrics and trim
- Removes solvent soluble soil such as oil, grease and pigments
- Aids in removing water-soluble soil with an effective detergent
- Virtually odorless
- Compatible with fabric-finish additives for restoring body to garments



Proven performance

DF-2000[™] dry cleaning solvent is manufactured to meet high standards of consistency and purity for highquality results every time. When used in conjunction with properly designed machinery, cleaning processes and additives, it provides cleaning performance comparable to perchloroethylene and other alternatives currently available.

Proven reliability

DF-2000 dry cleaning solvent delivers consistent cleaning performance with no reformulations or stability problems. Reliable, safe and time-tested, it offers:

- No moisture build-up which can cause shrinkage and or water soluble dye bleeding
- · Minimal post spotting when a detergent is properly used in a correctly designed process
- · Stability through multiple distillation and reclamation cycles
- · Controlled solvent composition for consistent, premium quality
- Cost-effective dry cleaning solvent solution

Properties	Test Methods	Sales Specifications
Appearance	Visual	Pass
Aromatics content (wt.%)	AM-S 140.31	0.02 max
Bulk Odor	BTQAL – 018	Pass
Color (Saybolt Units)	ASTM D 6045 or ASTM D 156	30 min
Flash point (°C)	ASTM D 56	60 min
Specific Gravity @ 15.6/15.6°C	ASTM D 4052	0.760 – 0.775

*This product contains approximately 7ppm BHT as added to the manufacturing site certified storage tank





Contact us for more information:

exxonmobilchemical.com df2000.com ©2015 ExconMobil. ExconMobil, the ExconMobil logo, the interlocking "X" device and other product or service names used herein are trademarks of ExconMobil, unless indicated otherwise. This document may not be distributed, displayed, copied or altered without ExconMobil's prior written authorization. To the extent ExconMobil authorizes distributed, including all of its headers, footers, disclaimers and other information. You may not copy this document to or reproduce it in whole or in part on a website. ExconMobil does not guarantee the typical (or other) values. Any data included herein is based upon analysis of representative samples and not the actual product shipped. The information in this document relates only to the named product or materials when not in combination with any other product or materials. We based the information on data believed to be reliable on the date compiled, but we do not represent, warrant, or otherwise guarantee, expressly or impliedly, the merchantability, fitness for a particular purpose, freedom from patert infringement, suitability, accuracy, reliability, or completeness of this information or the product and any processes in its territories of interest. We expressly disclaim liability for any loss, damage or injury directly or indirectly suffered or incurred as a result of or related to anyone using or relying on any of the information in this document. This document is not an endorsement of any non-ExconMobil product or process, and we expressly disclaim any contrary implication. The terms "we," "our," "ExonMobil Chemical Company, ExxonMobil and processing and may include any one or more of ExxonMobil Chemical Company, ExxonMobil Chemical, or any affiliate either directly or indirectly stewarded.